## (P) POWERED BY AQUATECH 3000 HP Land Drilling Rig

Year Modified: 2009

Rated Drilling Depth

5 in. Drill Pipe: 25.000 ft (7.619 m) 4-1/2 in. Drill Pipe: 29.000 ft (8.838 m)

Mast

Make: Parco

Height and Type: 156 ft (47.5 m), cantilever

Max. Hookload: 1.5 million lbs

Racking Capacity: 5 in. drill pipe. 96 feet stand -

21,000 feet (6,402 m)

**Drawworks** 

Continental Emsco C-3 Make: 3,000 hp (2,237 kW) Rated Input:

Input Power: Three (3) GE 752 motors, rated

1,000 hp (746 kW) each

1-3/4 in. (44.5 mm) Drilling Line:

**Traveling Equipment** 

Traveling Block: Ideco

Max. Load: 1.5 million lbs

Substructure

Make: Parco Clear Working Height: 24 ft (7.3 m) Setback Load: 975.000 lbs

**Rotary Equipment** 

Top Drive: Canrig 1165E - 650 ton

Input Power: GE 752 Shunt Wound continuous

amperage electric motor, 1,165 hp

(868 kW)

Rotary Table: Continental Emsco 37-1/2" (952.5 mm)

Input Power: One (1) GE-752 direct current

motor rated 1,000 hp

1.4 million lbs Static Load Rating:

**BOP System** 

**Annular Preventers:** One (1) 21-1/4 in. Hydril 2,000 psi

One (1) 13 5/8 in. Hydril 5,000 psi

Ram Preventers: One (1) 13-5/8 in. Cameron 10,000

psi Type U single rams

One (1) 13-5/8 in. Cameron 10,000

psi Type U double ram



**Gensets** 

Generators:

Five (5) Caterpillar 3512B diesel Engines:

> engines; 1,476 hp (1,101 kW) each Five (5) Caterpillar SR4B generators,

1,050 kW (1,500 kVA) each

**Power Distribution** 

Gen. Control: Five (5) Ross Hill Model 1400 SCR: Five (5) Ross Hill Model 1400

SCR bays

MCC: 600/480/220/127 volts

**Mud Pumps** 

High Pressure System: One (1) 7,500 psi high pressure

circulation system, dual mud lines to

ria floor

Pumps: Two (2) Continental Emsco FC-2200

triplex pumps; each rated 2,200 hp

(1,628 kW)

One (1) Continental Emsco FC-1600

triplex pump; rated 1,600 hp

(1,193 kW)

Input Power: Two (2) GE-752 traction motors for

FC-1600 pump rated at 800 HP each

(597 KW)

Two (2) GE 752 Hi-torque motors for

each FC-2200 pump rated at 1100 HP

each (821 KW)

**Mud Handling/Solids Control** 

Mud System Capacity: 1,980 bbls (315 m3)

Shale Shakers: Four (4) Derrick FLC 2000 shakers;

1,000 gpm each

One (1) Derrick Hi-G Dryer; 500 gpm

Swaco vacuum-type Degasser:



## **Rig Plot Plan**

